
New Consistency Checks and Implementing Online/Offline Yao

Joint work with: Asaf Cohen, Moriya Farbstein and Yehuda Lindell.

Part 1: Background

Recap: The Cut-and-Choose Technique



Checks the "opened" garbled circuits, evaluates the rest.

 2^{-s} security, while running an additional, lighter 2PC with 3s small garbled circuits for *cheating recovery* [Lindell-13].

Recap: Protecting Against Selective OT Attacks

Technique	Complexity	Assumptions	
Cut-and-choose OT	$\mathcal{O}(\mathit{ns})$ exponentia-	DDH	
	tions		
Randomized Encoding	$\mathcal{O}(n)$ OTs, $\mathcal{O}(ns^2)$	Standard	
	encryptions		
+ OT-Ext.,Free-XOR	$\mathcal{O}(s)$ OTs, $\mathcal{O}(ns)$	Free-XOR, etc	
	encryptions		

where n is Alice's input length, and s is a security parameter.

Recap: Protecting Against Selective OT Attacks

Technique	Complexity	Assumptions	
Cut-and-choose OT	$\mathcal{O}(\mathit{ns})$ exponentia-	DDH	
	tions		
Randomized Encoding	$\mathcal{O}(n)$ OTs, $\mathcal{O}(ns^2)$	Standard	
	encryptions		
+ OT-Ext.,Free-XOR	$\mathcal{O}(s)$ OTs, $\mathcal{O}(ns)$	Free-XOR, etc	
	encryptions		

where n is Alice's input length, and s is a security parameter.

(Open: Can we get optimal complexity with standard assumptions?)

Recap: Checking Bob's Input Consistency

Technique	Complexity	Assumption	Drawback	
DDH ZK	$\mathcal{O}(ns)$ exp.	DDH	Efficiency	
[Mohassel-R-13]	$\mathcal{O}(s)$ OTs, $\mathcal{O}(ns)$	ROM	Complicated	
	encryptions			
[shelat-Shen-13]	$\mathcal{O}(\mathit{ns})$ encryp-	Free-XOR*	Offline/Online	
	tions		setting	

where n is Bob's input length, and s is a security parameter.

Recap: Checking Bob's Input Consistency


Technique	Complexity	Assumption	Drawback	
DDH ZK	$\mathcal{O}(ns)$ exp.	DDH	Efficiency	
[Mohassel-R-13]	$\mathcal{O}(s)$ OTs, $\mathcal{O}(ns)$	ROM	Complicated	
	encryptions			
[shelat-Shen-13]	$\mathcal{O}(\mathit{ns})$ encryp-	Free-XOR*	Offline/Online	
	tions		setting	

where n is Bob's input length, and s is a security parameter.


The goal is to verify consistency ONLY between good circuits!

Part 2: A New Consistency Check


Start with Standard GCs



For example ...




Commit on Input Labels and Masks




- Orange rectangle = standard commitment.
- ▶ Blue rectangle = commitment that also allows decommiting the XOR of two commitments:
 - ▶ Given HCom(m), $HCom(m') \rightarrow can decommit <math>m \oplus m'$.


The Cut-and-Choose



Say that Bob's Input is y = 11



Repeating the Steps



Implementing HCom(·) Efficiently [Rabin et al-12]

Committing on $m \in \{0,1\}^n$

- ▶ Pick $m_0 \in \{0,1\}^n$ at random. Let $m_1 = m_0 \oplus m$.
- ▶ Send $Com(m_0)$ and $Com(m_1)$.

Implementing HCom(·) Efficiently [Rabin et al-12]

Committing on $m \in \{0,1\}^n$

- ▶ Pick $m_0 \in \{0,1\}^n$ at random. Let $m_1 = m_0 \oplus m$.
- ▶ Send $Com(m_0)$ and $Com(m_1)$.


Decommitting XOR of two commitments

Let m_0^1 , m_1^1 and m_0^2 , m_1^2 be the committed values.

- ▶ Sender sends $M_0 = m_0^1 \oplus m_0^2$ and $M_1 = m_1^1 \oplus m_1^2$.
- Receiver sends a random bit b.
- ► Sender decommits m_b^1 and m_b^2 .
- ▶ Receiver verifies that $M_b = m_b^1 \oplus m_b^2$ and outputs $M_0 \oplus M_1$.

Improving Security of XOR Decommitment

Use k pairs of commitments for soundness 2^{-k} . For example, with k = 4,



where $M_0^i \oplus M_1^i$ should be the same for $i = 1, \dots, 4$.

Improving Security of XOR Decommitment

Use k pairs of commitments for soundness 2^{-k} . For example, with k = 4,

where $M_0^i \oplus M_1^i$ should be the same for $i=1,\ldots,4$.

Performance and Assumptions

Performance.

When the commitment's message domain is large, the number of commitments is amortized.

For example, for security parameter $k=40,\,80$ commitments are needed. If the message domain is 80-bit long, then the amortized number of commitments per input bit is 1!

Performance and Assumptions

Performance.

When the commitment's message domain is large, the number of commitments is amortized.

For example, for security parameter $k=40,\,80$ commitments are needed. If the message domain is 80-bit long, then the amortized number of commitments per input bit is 1!

Assumptions.

Option 1: DDH and any Com (but requires additional two exponentiations per circuit).

Option 2: ROM (without exponentiations).

Other Advantages

Much easier to implement than the method of [Mohassel-R-13].

Other Advantages

- Much easier to implement than the method of [Mohassel-R-13].
- ► Can be used in the Offline/Online 2PC protocols we have (as opposed to the method of [shelat-Shen-13]).

Part 3: Implementing Online/Offline Yao

The Offline/Online Setting

Offline stage: Inputs are unknown, but we are willing to work a bit harder. (The circuit in use is known.)

Online stage(s): Inputs are known, and we wish to compute the function with minimal latency once an input arrives.

Obviously, the running time of the online stage must depend on |C|.

Amortized Cut-and-Choose [Lindell-R-14, Huang et al-14]


Instead of a single 2PC execution, consider N executions. This allows us to amortize the cost of the checked-circuits over many executions.

- ▶ Amortized complexity of $\mathcal{O}(\frac{s}{\log N})$ garbled circuits per invoked 2PC.
- ▶ In the ROM, the communication of the online stage is independent of |C|. (Very significant in practice!)


The New Cut-and-Choose: Bob Sends Many GCs



The New Cut-and-Choose: Checking and Bucketing



The New Cut-and-Choose: Checking and Bucketing



How Many Circuits Are Needed?

N	total #circuits	#eval circuit per 2PC	#circuits per 2PC
10	200	11	20
32	351	8	10.96
	437	6	13.65
128	998	6	7.79
	1143	5	8.92
1024	5627	5	5.49
	5689	4	5.55
4096	18005	4	4.39
	25600	3	6.25

We can use the same technique also for checking the cheating recovery circuits.

- ► For 32 computations, only 30 garbled circuits are needed on average per execution.
- ▶ For 1024 computations, only 11.76 are needed.

(Recall that [Lindell-13] requires about 125 circuits.)

Prototype Implementation

- ▶ Designed a new protocol based on the protocol of [Lindell-R-14] and the new input-consistency check protocol. Heavily optimized in the ROM.
- Most steps are implemented using SCAPI. A number of CPU-intensive steps are implemented in C.
- ▶ Works with the recent OT-extension library of [Asharov et al-15] and a new library for fixed-key garbling.

Performance

Circuit	#executions	Offline		Online		
Circuit		total	per 2PC	1	4	8
ADD	32	8325	260	17	15	14
	128	19787	155	10	9	11
	1024	103170	101	7	7	-
AES	32	12244	383	32	27	25
	128	30766	240	21	19	18
	1024	159144	155	16	16	14
SHA-1	32	21157	661	71	62	42
	128	55762	436	48	-	40
	1024	331192	323	37	-	27

All times are in ms. Offline is with 8 threads (and is roughly 20% - 40% slower than with a single thread).

Four Orders of Magnitude in Six Years

How much has performance of cut-and-choose 2PC improved over the years?

2009: 1114 seconds.

2011: 264 seconds.

2012: 1.4 seconds (cluster with 512 nodes, s = 80).

2013: 40 seconds (cluster with 8 nodes, s = 80).

2014: 0.46 seconds (using GPUs).

2015: < 0.2 seconds (and ≤ 32 ms for online time).



2³!

Four Orders of Magnitude in Six Years

How much has performance of cut-and-choose 2PC improved over the years?

2009: 1114 seconds.

2011: 264 seconds.

2012: 1.4 seconds (cluster with 512 nodes, s = 80).

2013: 40 seconds (cluster with 8 nodes, s = 80).

2014: 0.46 seconds (using GPUs).

2015: < 0.2 seconds (and ≤ 32 ms for online time).



 $2^{3}!$

(How much lower can Online/Offline 2PC with GPUs get us?)